

PRODUCT REQUIREMENT SHEET	
See LV 75-032	
MEASURING VOLTAGE	120V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Vertical
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

See LV 75-032

MEASURING VOLTAGE	120V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Vertical
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	1000W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE	2500 K NA	± 100 K
FLUX (HeLeN lamp)	NA	
WEIGHT	36 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP INFRARED INDUSTRIAL 14209X 1000W 120V X-CLIP								9245 889 36300 0833/000			18/02/2011		
New															
REF. :		DOCUMENTATION		UNIT mm	PROJ EUROPE 		2 SH		SH	190-2		10		A4	
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															