

PRODUCT REQUIREMENT SHEET	
See LV 75-32	
MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Vertical
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

		VALUE UNIT	TOLERANCE
WATTAGE		1500W	± 6 %
LIFE		5000 h	average
COLOR TEMPERATURE	Clear lamp Lamp with reflector	2300 K * NA	± 100 K
FLUX (HeLeN lamp)	Clear lamp Reduction	10000 lm 99 %	Indicative value min
CAP INSULATION (WET)		2000 V	min
WEIGHT		63 g	

1 0833	2 0833	3 0000	4	5	6	7	8		
SUPERSEDES : 9245 937 45500 0833/000 p190-2 Of 30/06/2014		HALOGEN LAMP GARNETA 26002Z 1500W 235V				9245 937 45500 0833/000		16/08/2016	
REF. : PDM IRK 2016-040		DOCUMENTATION	UNIT mm	PROJ EUROP 	2 SH	SH	190-2	10	A4
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD			DR. FISCHER Europe				
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.									