

PRODUCT REQUIREMENT SHEET	
See LV 75-32	
MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	1000W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE	Clear lamp Lamp with reflector	± 100 K Indicative value
FLUX (HeLeN lamp)	Clear lamp Reduction	NA NA
MAXIMUN IRRADIANCE LEVEL AT 10 CM	7000 W/m²	Min
WEIGHT	54 g	

Project

1 0833	2 0833	3 0000	4	5	6	7	8		
SUPERSEDES : New		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 17023Z/83 1000W 235V REFL				9246 047 44900 0833/000		07/12/2015	
REF. : CRP 1542		DOCUMENTATION	UNIT mm	PROJ EUROPE 	2 SH	SH	190-2	10	A4
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD			DR. FISCHER Europe				
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.									