



# CorePro LED PLT 4P



## CorePro LED PLT HF 6.5W 830 4P GX24q-2

The CorePro LED PLT 4P integrates a LED light source into a traditional fluorescent form factor. This product is the ideal solution for uplampping in general lighting applications: it meets basic lighting requirements, offers significant energy savings, and is environmentally friendly

### Product data


General Information		Warm-up time to 60% light	
Cap-Base	GX24Q-2 [GX24q-2]		0.5 s
Nominal lifetime	30,000 hour(s)	Power Factor (Fraction)	0.9
Switching Cycle	200,000	Voltage (Nom)	20-60 V
Lighting Technology	LED	<b>Temperature</b>	
Flux measurement reference	Sphere	Ambient temperature range	-20 °C to 35 °C
<b>Light Technical</b>		T-Case Maximum (Nom)	65 °C
Color Code	830 [CCT of 3000K]	<b>Controls and Dimming</b>	
Beam Angle (Nom)	120 degree(s)	Dimmable	No
Luminous Flux	720 lumen	<b>Mechanical and Housing</b>	
Color Designation	White (WH)	Bulb Finish	Frosted
Correlated Color Temperature (Nom)	3000 K	Bulb Material	Plastic
Luminous Efficacy (rated) (Nom)	110 lm/W	Product Length	100 mm
Color Consistency	<6	Bulb Shape	Tube, single-ended
Color rendering index (CRI)	82	<b>Approval and Application</b>	
LLMF At End Of Nominal Lifetime (Nom)	70 %	Energy Efficiency Class	F
<b>Operating and Electrical</b>		Energy Saving Product	Yes
Line Frequency	20K-80K Hz	Approval Marks	RoHS compliance TUV CE marking KEMA Keur certificate
Input Frequency	20K-80K Hz	Energy Consumption kWh/1000 h	7 kWh
Power Consumption	6.5 W		
Starting Time (Nom)	0.5 s		

# CorePro LED PLT 4P

EPREL Registration Number	1361420
CE mark	Yes
EU RoHS compliant	Yes
<b>Product Data</b>	
Full product code	871951448776500
Order product name	CorePro LED PLT HF 6.5W 830 4P GX24q-2
Order code	929003576302


Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	20
Material number (12NC)	929003576302
Full product name	CorePro LED PLT HF 6.5W 830 4P GX24q-2
EAN/UPC - Case	8719514487772

## Dimensional drawing




Product	D1	D2	A1	A2	A3
CorePro LED PLT HF 6.5W 830 4P GX24q-2	42 mm		93 mm	103 mm	119 mm

## Photometric data




© 2023 Osram Opto Semiconductors AG | Philips Lighting B.V. | Page 11



## General uniform lighting - CorePro LED PLT HF 6.5W 830 4P GX24q-2



## Light Distribution Diagram



## Spectral Power Distribution Colour



# CorePro LED PLT 4P

## Lifetime




Lumen Maintenance Diagram

Life Expectancy Diagram - CorePro LED PLT HF 6.5W 830 4P GX24q-2



Life Expectancy Diagram

Life Expectancy Diagram



Lumen Maintenance Diagram - CorePro LED PLT HF 6.5W 830 4P GX24q-2

## CorePro LED PLT 4P

