



Philips TUV Amalgam XPT System

Philips TUV Amalgam XPT system consists of an electronic driver that operates one TUV Amalgam XPT lamp, mounted in a sleeve. The electrical specifications are tailored to the lamp, ensuring an optimized performance of the Philips TUV Amalgam XPT system. Thanks to extensive testing before a lamp system is released, we can ensure maximum reliability and long lifetime.

Main applications

- Deactivation of bacteria, viruses and other micro-organisms
- Municipal drinking water treatment equipment
- Municipal waste water treatment equipment
- Process water treatment equipment
- Swimming pool units
- Equipment for the production of ultra-pure water; for example for the semiconductor, pharmaceuticals and cosmetics industries (ozone version)

Features

Short-wave UV radiation with a peak at 253.7 nm (UVC) for disinfection

Special amalgam used for highest efficiency over wide temperature range

Protective inside coating ensures constant UV output over the complete lifetime of the lamp

Philips electronic driver available for a perfect interface

Minimized amount of mercury

Universal burning position possible for the T6 range, depending on lamp type and sleeve dimensions

Tailor-made solutions possible

Lamp can be made from special quartz (open / synthetic) to maximize 185nm Ozone generation

Benefits

Effective disinfection over the useful lifetime of the lamp

Approximately 10% energy savings, because lamps can be dimmed to reach the same UV output compared to similar lamps on the market

High system efficacy because it is not required to over-design the purification system to maintain effectiveness of disinfection

Best environmental choice because of long reliable life, less waste and industry leading low amount of mercury

Extreme reliability of driver, with annual failure rate of less than 1%

High efficiency during dimming thanks to unique amalgam temperature control of the 800W lamps


Technical data

Lamp type	Cap base	Dim. no	Technical Wattage (W)	Lamp Voltage (W)	Lamp Current (W)	Useful life (W)	UVC ¹ at 0h (W)	UVC ¹ at 100h (W)	Depreciation at useful lifetime (%)	Ordering number 12 NC
TUV 130W XPT SE	4 Pins Single Ended	1	140	67	2.1	12000	46	44	15	928101805112
TUV 180W XPT SE	4 Pins Single Ended	2	180	90	2.1	12000	63	60	15	928106805112
TUV 200W XPT SE	4 Pins Single Ended	3	200	94	2.1	12000	66	63	15	928106905112
TUV 325W XPT HO SE	4 Pins Single Ended	4	305	160	2.0	12000	114	108	15	928107005112
TUV 330W XPT SE	4 Pins Single Ended	5	275	78	3.6	12000	96	91	15	928101705112
TUV 800W XPT SE	4 Pins Single Ended	6	815	103	8.0	12000	273	254	15	928107605112

¹ nominal UVC output (fixed current)

Lamp type	Driver	Ordering number 9137...
TUV 130W XPT SE	TUV 130W XPT driver	00729703
TUV 180W XPT SE	TUV 180-200W XPT driver	10054695
TUV 200W XPTSE	TUV 180-200W XPT driver	10054695
TUV 325W XPT HO SE	TUV 325W XPT (HO) driver	10054995
TUV 330W XPT SE	-	-
TUV 800W XPT SE	TUV 800W XPT driver	Prototype

All drivers are pre-heat and dimmable from 100 to 50%.



4 Pins Single Ended

Dim.* no.	A nom.	B nom.	C max.
1	19	740	842
2	19	930	1032
3	19	1040	1147
4	19	1480	1582
5	32	1440	1554
6	38	1609	1791

* Dimensions (mm)