

## XBO 150 W/4

XBO  $\leq$  450W Double End | Intense point source that provides a broad, continuous spectrum and has near perfect color rendering in the visible range



### Areas of application


- Endoscopy
- Microscopy
- Surgical Headlamps
- Fiber Illumination
- Solar Simulation
- Imaging & Scanning

### Product family benefits

- Very high luminance (point light source)
- Continual color quality, irrespective of lamp type and lamp wattage
- Constant light color throughout the life of the lamp
- Long lamp life

### Product family features

- Color temperature: approx. 6,000 K (Daylight)
- High color rendering index:  $R_a >$
- Continuous spectrum in the visible range
- High arc stability
- Hot restart capability
- Dimmable
- Instant light on starting



Technical data

General Product Information

Global order reference	XBO 150W/4
Product number (Americas)	69238
Product name (Americas)	XBO 150W/4 20V 10/CS 1/SKU
Family brand	XBO
Lamp type	DOUBLE ENDED
Product remark	Lamp uses a special quality of quartz glass, known as SUPRASIL, which – in comparison to conventional quartz – provides higher transmission below 250 nm

Electrical Data

Nominal wattage	150 W
Lamp voltage	17...21 V <sup>1)</sup>
Lamp current	7.5 A
Type of current	DC

<sup>1)</sup> Initial voltage range

Photometric Data

Nominal luminous flux	3000 lm
Luminous intensity	300 cd <sup>1)</sup>
Color temperature	6000 K
Color rendering index Ra	98
Light center length (LCL)	57.0 mm

<sup>1)</sup> Typical initial photometric value

Physical Attributes & Dimensions

Electrode gap (cold)	2.5 mm
Base (anode)	SFc12-4
Base (cathode)	SFcX12-4
Diameter (in)	39.331 in
Diameter	20.0 mm
Length	150.0 mm
Product weight	100.00 g

Operating Conditions

Burning position	≤15° <sup>1)</sup>
Cooling	Forced

<sup>1)</sup> Anode (+) on top

Product datasheet

Lifetime Data

Nominal lifetime	1200 hr
Average life - vertical	1200 hr

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4050300508382
Date of declaration	16-08-2024
Declaration no. in SCIP database	233c237a-3183-44a5-b9da-6dd186a65e22
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300508382	OSRXBO1504	-	-	-

# Product datasheet

## Safety advice

Because of their high luminance, UV radiation and high internal pressure in both the hot and cold state, XBO lamps must only be operated in appropriate enclosed casings. Always use the protective jackets supplied when handling these lamps. They may only be used as open lamps if appropriate safety measures are taken. More information is available on request or can be found in the leaflet included with the lamp or the operating instructions.

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300508382	XBO 150 W/4		224 mm x 95 mm x 60 mm	1.28 dm <sup>3</sup>	186.00 g
4050300508399	XBO 150 W/4	Shipping carton box 10	306 mm x 235 mm x 200 mm	14.38 dm <sup>3</sup>	2245.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.