

64223 10W 6V 40/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Product datasheet

Technical data

General product information

Product Number	54245
Product Name	64223 10W 6V 40/CS 1/SKU
Application	Projector
LIF Code	M/43

Electrical data

Nominal Wattage	10 W
Nominal Voltage	6 V
Type of Current	AC

Light technical data

Luminous Flux	150 lm
Light Center Length - LCL (in)	0.936 in
Light Center Length - LCL (mm)	24 mm
Color Temperature	2900 K
Color Rendering Index	100
Average Rated Life	300 h


Physical attributes

Base	G4 BIPIN
Bulb Shape	T9
Maximum Overall Length (in)	1.482 in
Maximum Overall Length (mm)	38 mm
Length l (in)	1.482 in
Length l (mm)	38 mm
Diameter d (in)	0.354 in
Diameter d (mm)	9.00 mm
Distance a (in)	0.936 in
Distance a (mm)	24 mm
Filament Dimensions Length (in)	0.0270 in
Filament Dimensions Length (mm)	0.7 mm
Filament Dimensions Width (in)	0.059 in
Filament Dimensions Width (mm)	1.5 mm
Reflector Coating	9.00

Additional product data

Product datasheet

Operating Position	Any
Class	C (gas)



s180

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54245	4008321107039	Folding box (SKU)	1	1 in x 0.9 in x 2.8 in	
54245	4008321107046	Shipping box (Case)	40	5.7 in x 4.2 in x 4.8 in	0.5 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.