

## 64380

6.6 A Current Controlled Halogen - Double End Lamps for Series Operation | Double end 6.6 A current controlled lamps designed specifically for airfield fixtures



### Areas of application


- Airfield Lighting

### Product family benefits

- Reduced operation and maintenance costs due to long lifetime
- Instant and constant light output over the lamp life
- Flicker-free operation
- Mercury-free

### Product family features

- Dimmable
- Infrared radiation output that provides light in the worst of conditions



Technical data

General Product Information

Global order reference	64380 200W 6.6A
Lamp type	SINGLE ENDED
LIF code	J1/40

Electrical Data

Nominal wattage	200 W
Nominal current	6.60 A
Type of current	AC

Photometric Data

Nominal luminous flux	4400 lm
Color temperature	2800 K
Color rendering index Ra	100

Physical Attributes & Dimensions

Lamp base	R7s-18
Diameter (in)	0.591 in
Diameter	15.0 mm
Length	65.6 mm
Length with base excl. base pins/connection	65.00 mm
Product weight	6.00 g

Operating Conditions

Burning position	p15
------------------	-----

Lifetime Data

Nominal lifetime	1000 hr
------------------	---------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4050300209944   0046135587078
Date of declaration	09-07-2024
Declaration no. in SCIP database	In work
Candidate list substance 1	No declarable substances contained

# Product datasheet

## Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300209951	64380		- x - x -	4.21 dm <sup>3</sup>	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.